

DESCRIPTION

Johnstone's Trade Aqua Gloss is an innovative, water based, high sheen gloss, for use on interior and exterior wood and metals. It looks, feels and applies more like a traditional gloss, but is quick drying - reducing application times, has a low odour and contains less atmospheric polluting VOC's.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Ideal for interior and exterior wood and metal.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Gloss.

VOLUME SOLID

41.9%

COVERAGE



Johnstone's Trade Aqua Gloss will cover approximately 10-12 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 91µm, dry: 38µm.

DRYING TIME



Touch dry in 1-2 hours.
Recoat after 4-6 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

CLEANER

Cleaner: Clean water

VOC CONTENT

EU limit value for this product (Cat A/d): 130g/l (2010).

This product contains max 50g/l VOC.



KEY PROPERTIES

- Tough, durable & quick drying
- Low odour, water based technology
- Excellent application & finish

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare wood with Johnstone's Trade Aqua Undercoat. Prime all other bare surfaces with the appropriate Johnstone's Trade primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Apply one full coat of Johnstone's Trade Aqua Undercoat to all correctly prepared and primed surfaces before application of Johnstone's Trade Aqua Gloss. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Stir well before use. Easy to apply by brush. Avoid overspreading. Do not apply in temperatures below 10°C or externally when rain is imminent. For best results use a synthetic brush.

CLEANING



Remove as much product as possible from application equipment before cleaning. To maintain brushes, do not allow paint to dry out on bristles. Regularly wash in clean, cold soapy water throughout use. Following prolonged use, clean with Clean Spirit, Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available: www.johnstonestrade.com or call 01924 354354

SIZES

1 Litre, 2.5 Litre, 5 Litre.