

DESCRIPTION

Johnstone's Trade Woodworks Quick Dry Satin Woodstain has been specially formulated to protect and stain smooth planed hard and soft woods. This water based, quick drying formulation ensures that most tasks can be completed in one day. For maximum protection on new, bare and untreated wood first apply a suitable wood preserver.

COLOUR RANGE

Clear; Light Oak; Jacobean Oak; Redwood; Mahogany; Ebony; Medium Oak; Walnut; Pine; Antique Pine; Rosewood; and Teak.

A Range of colours available in 2.5 litre only via the Johnstone's CMS2010 Tinting System.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPES OF SUBSTRATE

Doors, window frames, fascia boards, cladding, garden furniture.

COVERAGE



Johnstone's Trade Woodworks Quick Dry Satin Woodstain will cover approximately 12 square metres per litre depending on the nature and porosity of the wood.

DRYING TIME



Touch dry in 1 hour. Recoatable after 4 hours. Allow longer in adverse conditions.

TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure, upright position. PROTECT FROM FROST.

THINNER

Thinner: Clean Water.

VOC CONTENT

EU limit value for this product (Cat A/e): 130g/l (2010). This product contains max 80g/l VOC.



KEY PROPERTIES

- Resists cracking, blistering and peeling
- Allows wood to breathe and moisture to escape
- Showerproof in 1 hour
- Six years weather protection

PREPARATION

Ensure all surfaces to be stained are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any resins and natural oils using White Spirit. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Do not prepare the surface using steel wool. Avoid inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. Note: Not suitable for use on Linseed Oil Putty, may be used on wooden glazed beads. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Stir Johnstone's Trade Woodworks Quick Dry Satin Woodstain thoroughly prior to use. Apply evenly by brush along the grain, paying particular attention to end grain. Do not overlap the brush strokes. On bare or new wood the first coat can be thinned with one part water to nine parts Johnstone's Trade Woodworks Quick Dry Satin Woodstain followed by two coats of undiluted Johnstone's Trade Woodworks Quick Dry Satin Woodstain. Do not apply when air or surface temperatures are below 10°C, in damp conditions or if rain is imminent. PLEASE NOTE: The final colour will depend on the original colour of the wood and the number of coats applied. The colour label on this tin indicates approximate colour only.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean application equipment immediately after use with warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

750ml and 2.5 Litre.